


CR C0258

Request identity number:	C0258
Type of request:	Technically new
Proposal:	To introduce a new symbol for contact.
Reason:	<p>The proposed symbol has been frequently used in industries.</p> <p>The proposed combination graphical symbol can be composed of a couple of symbols as already standardized combination symbols are expressed in similar ways.</p> <p>There is no other applicable symbol in IEC 60617.</p>
Requested by:	Hiroaki Ikeda ikeda@faculty.chiba-u.jp JP

Symbol identity number:	S01911	
Drawing:		
Earlier published in:	–	
Description (temporary field)	EN	Break contact, delayed both when the device containing the contact is being activated and when it is being de-activated.
	FR	
Name:	EN	Break contact, delayed
	FR	Contact à ouverture, retardé
Alternative names:	EN	–
	FR	–
Keywords:	EN	contacts, switches
	FR	contacts, interrupteurs
Form:	EN	–
	FR	–
Alternative forms:	–	
Applied in:	–	
Applies:	S00148, S00149, S00229	
Application notes:	A00060, A00061, A00070	
Source references:	–	
Published in:	–	
Entered on:	–	
Evaluated on:	–	
Released on:	–	
Rejected on:	–	
Obsolete from:	–	
Proposed by:	JP	
Replaces:	–	
Replaced by:	–	
Shape class:	Half-circles, Lines	
Function class:	K Processing signals or information	
Application class:	Circuit diagrams, Connection diagrams, Function diagrams, Overview diagrams	

Symbol restrictions:	EN	–
	FR	–
Remarks:	EN	The contact is delayed both when the device containing the contact is being activated and when it is being de-activated.
	FR	Le contact est retardé à la fois lorsque le dispositif contenant le contact est activé et lorsqu'il n'est plus activé.
Change Request:		C0258